

03





VENTILATION



ROOF FANS

MODELS	UNIT	PFF5500	PFF6000
AIR FLOW RATE	m ³ /h	560	970
POWER SUPPLY	V/Hz	230V 50-60Hz	
DIMENSIONS	mm	364x364x107	
POWER CONSUMPTION	W	58/75	85/90
CURRENT CONSUMPTION	A	0.26/0.34	0.38/0.44
OVERCURRENT PROTECTION	-	THERMAL	
ELECTRICAL CONNECTION	-	4-POLE TERMINAL 2.5mm ²	
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	
NOISE LEVEL	dB(A)	62 (64)	72 (73)
FLOW DIRECTION	-	INSIDE / OUT	
BEARING	-	BALL	
SERVICE LIFE	Hour	50.000	
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
WEIGHT	kg	3.16	3.74
MOUNTING	-	8 PCS M4 SCREWS	
CONFORMITY	-	CE	





PF1000



PTF1000







PTF1000

FILTER FANS

30m³/h

MODELS	UNIT	PF1000	PTF1000
AIR FLOW RATE	m ³ /h	-	30 (41)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	110x110x20.5	110x110x58.5
POWER CONSUMPTION	W	-	14 (13)
CURRENT CONSUMPTION	A	-	0.08/0.07
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	LEAD WIRE
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	62 (64)	28 (31)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	SLEEVE
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	SELF-ADHESIVE	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.10	0.40
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	





PFI1500





PTF1500



PTF1500

**FILTER
FANS**
100 m³/h

MODELS	UNIT	PFI1500	PTF1500
AIR FLOW RATE	m ³ /h	-	100 (140)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	160x160x31	160x160x69
POWER CONSUMPTION	W	-	26 (23)
CURRENT CONSUMPTION	A	-	0.14/0.13
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	LEAD WIRE
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	42 (46)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.18	0.68
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	





PFI2500






PTF2500



PTF2500

FILTER FANS 115m³/h

MODELS	UNIT	PFI2500	PTF2500
AIR FLOW RATE	m ³ /h	-	115 (130)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	260x260x31	260x260x103
POWER CONSUMPTION	W	-	26 (23)
CURRENT CONSUMPTION	A	-	0.14/0.13
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	3-POLE TERMINAL
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	42 (46)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.48	1.18
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	





PFI2500






PTF3500



PTF3500

FILTER FANS 240m³/h

MODELS	UNIT	PFI2500	PTF3500
AIR FLOW RATE	m ³ /h	-	240 (270)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	260x260x31	260x260x103
POWER CONSUMPTION	W	-	37 (35)
CURRENT CONSUMPTION	A	-	0.23/0.22
OVERCURRENT PROTECTION	-	-	IMPEDANCE
ELECTRICAL CONNECTION	-	-	3-POLE TERMINAL
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	52 (53)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.48	1.60
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	





PFI2500





PTF4500



PTF4500

FILTER FANS *650m³/h*

MODELS	UNIT	PFI2500	PTF4500
AIR FLOW RATE	m ³ /h	-	650 (900)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	260x260x31	260x260x111
POWER CONSUMPTION	W	-	66 (75)
CURRENT CONSUMPTION	A	-	0.35/0.38
OVERCURRENT PROTECTION	-	-	THERMAL
ELECTRICAL CONNECTION	-	-	4-POLE TERMINAL
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	60 (63)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.48	2.84
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	





PFI3000



PTF5000



PTF5000

FILTER FANS

850m³/h

MODELS	UNIT	PFI3000	PTF5000
AIR FLOW RATE	m ³ /h	-	850 (1200)
POWER SUPPLY	V/Hz	-	230V 50-60Hz
DIMENSIONS	mm	325x325x31	325x325x111
POWER CONSUMPTION	W	-	110 (140)
CURRENT CONSUMPTION	A	-	0.350/0.72
OVERCURRENT PROTECTION	-	-	THERMAL
ELECTRICAL CONNECTION	-	-	4-POLE TERMINAL
OPERATING TEMPERATURE	°C	-10/+70	
PROTECTION DEGREE	-	IP54	IP54 / CLASS I
NOISE LEVEL	dB(A)	-	65 (68)
FLOW DIRECTION	-	-	OUTSIDE-IN
BEARING	-	-	BALL
PLASTIC MATERIAL	-	UL94 V0 ABS FLAME RETARDANT	
GASKET	-	POLYURETHANE SEALING	
COLOUR	-	RAL7035 (RAL7032 ON REQUEST)	
WEIGHT	kg	0.70	4.12
MOUNTING	-	FAST CLIP-ON	
CONFORMITY	-	CE	

